
Voice and data flat plate without dust cover for 1 element with 2 RJ45 connectors category 5e FTP white Simon K45

REF. **KB095F/9**



BASIC INFORMATION

DESCRIPTION

Elements of the plate for 1 and 2 RJ45 connectors model KB095F / 9 professional range of products for installations. Simon K45. High capacity for compatibilizar with other elements of the same series Simon K45. Voice and data flat plate without Dust cover with 1 element and 2 RJ45 category 5e FTP connectors with The format of snap-fit Keystone I, II, ATT ® / Avaya ® comes with insertion tool Model. It is an individual version and complex modular medium, with colours In white and shades. This made with thermoplastic components free Insulation, which, which minimizes the risk in situations of fire and smoke. Element of dimensions 45x45mm. Depth of 8,5mm, in case of voice and data plates vertical enclosures There are the need to use the 90 ° positioner (ref. K66) to guide the plate into a vertical position.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Voice and data flat plate without dust cover, RJ45 category 5e FTP connectors

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-24 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 5e FTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
No

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
9003

RJ45 ADAPTOR MODULE
Included in voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.042

PRODUCT NET WEIGHT
0.042

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436032026

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
118

PACKAGING WIDTH
121

PACKAGING LENGTH
264

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3769392

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.42

PACKAGING NET WEIGHT
0.42

PACKAGING WEIGHT UNIT
KGM