

Adjustable depth trap for 4 S-modules to be installed in a false floor gray Simon CIMA

REF. SF410/1



BASIC INFORMATION

FINISH

Grey

MATERIAL

Various

COMPATIBILITY

With mechanisms Simon Cima
and Simon 27 Play/Simon K45
(via adapter)

ETIM CLASS

EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES

12

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1300kg

RAL

7011

RECESS DIMENSION (MM)

170 x 265 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

REMOVAL OF THE FRAME

Only with tool

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436052598

PRODUCT NET WEIGHT

1.645

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

4982940

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436052598

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.65

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

1.645

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

186

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

1.645

PACKAGING LENGTH

282