

Framework for 2 elements in adjustable floor box white Simon 500 Cima

REF. 52051801-030



BASIC INFORMATION

DESCRIPTION

The new frame holder mechanisms for two elements in adjustable floor box Simon 500 Cima in White, has a more integrated design and appeal response to the most innovative on the market, with the versatility of an installation suitable for both recessed in concrete floor and raised floor, the frame holder for Simon 500 Cima, is composed of halogen-free thermoplastic that prevents the no flame propagation and toxicity by smoke in case of fire. Thanks to the thermoplastic, the frame holder for Simon 500 Cima, you can reach temperatures ranging from -5 °C and 60 °C and even brush the most of 90 °C. With a size of 132 x 76 x 16 mm, a design of clean lines and minimalist, its finishes in a white tones and the ease of installation and usability, the frame holder for Simon 500 Cima, it is the perfect solution to give your room of the greater security, innovation and style.

FINISH

White

COMPATIBILITY

Simon 500 Cima and Simon 27
Play/Simon K45 mechanisms
(using a specific adaptor)

PACKAGING CONTENTS

Framework

MATERIAL

Plastic

ETIM CLASS

EC000007

REMARKS

The adjustable floor boxes include the framework. You only need to order it as a spare part in the event of breakage or loss.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

HEAT RESISTANCE (°C)

+125°C (according rule IEC
60695-10-2)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

2, 4, 6 and 8 elements

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

NUMBER OF MODULES

2 modules

DIELECTRIC STRENGTH

No holes or contours, with 2000V
at 50 Hz for 1 minute

KIT AVAILABILITY

No

RAL

9003

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

VERSION

2 elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using screws

INSTALLATION DIRECTION

Horizontal, Vertical

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

In concrete floor and raised floor through the adjustable floor boxes

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053093214

PACKAGING VOLUME

2871375

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

95

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.05

PACKAGING WIDTH

155

PACKAGING NET WEIGHT

0.5

PRODUCT NET WEIGHT

0.05

PACKAGING LENGTH

195

PACKAGING WEIGHT UNIT

KGM

