

French socket outlet 16A 250V~ with safety device, indicator light and screw terminal connection white Simon K45

REF. KL02/9



BASIC INFORMATION

DESCRIPTION

French socket outlet from the Simon K45 range manufactured in white. It has a screw terminal connection and a safety device. Its current is 16A and voltage 250V and it also has 2 modules. It measures 45x45x39 mm and allows a cable section of 1.5 to 2.5 mm and wire stripping of 12 mm. Manufactured with metal components, halogen-free and with self-extinguishing thermoplastic insulation, this Simon K45 socket outlet guarantees no flame spread in case of fire and low toxicity if there is smoke. It has been designed in compliance with the regulations UNE 20315-1-1:2009 + 20315-1-2:2009 + NF C-61314:2008 + A1:2010 and is a socket outlet suitable for both surface and flush mounting.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

socket plug with trim cover and indicator light

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

1,5 to 2,5 mm

AVAILABLE IN

Shucko and french format

NUMBER OF CONNECTIONS PER TERMINAL

2 connections per terminal (1 input / 1 output)

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

FORMAT

French

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INDICATOR FUNCTION

Yes

INSULATION RESISTANCE (V-MΩ)

>5M? At 500 V

CURRENT (A)

16 A

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 a 60° C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

2 modules

MONOBLOCK

No

RAL

9003

NUMBER OF SOCKETS

1

VERSION

Single

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor ref.50012088-030

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

NUMBER OF TERMINALS

3 inputs / outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.05

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

1212505

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053123690

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

121251

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.5

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

49

PACKAGING NET WEIGHT

0.5

UNITARY PACKAGING GROSS

WEIGHT

0.05

PACKAGING WIDTH

101

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

245