Trim plate for 1 SUB-D25 connector (parallel port) for 2 elements black Simon K45

REF. **K104/14**



BASIC INFORMATION

DESCRIPTION

Trim plate for 1 SUB-D25 connector (parallel port) of 2 elements finished in black, the piece is included in the Simon 27 series, a collection designed to improve the multimedia connections in all spaces. It is made of halogen-free thermoplastic, a material that guarantees no flame spread in case of fire in the event of a fire, as well as the minimum toxicity if there is the presence of gas. This plate measures 45x90x8,5 mm comes with housings for fastening the connector using screws with a hexagonal profile for SUB-D9-Way connectors. The connector is not included and must be ordered by expected. It offers a high thermal resistance and can be installed in environments between -5 and 60 ° for optimum conservation. With regard to its maintenance, it is best to give light passages with a dry and soft cloth. Remember that it is not advisable to use abrasive cleaners, as they may damage the plate.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Plate for 1 SUB-D25 connector

ETIM CLASS

EC000018

REMARKS

The plate includes housings for fastening the connector using screws with a hexagonal profile for D-SUB-connectors. The connector is not included (must be ordered separately).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

Version with 1 SUB-D25 connector with soldered connection

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

FORMAT

Sub-D25

INDICATOR FUNCTION

No

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF MODULES

1 module

RAL

7021

VERSION

Single

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

REMOVAL OF THE PLATE

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.021

PRODUCT NET WEIGHT
0.021

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436038189

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
2.05

PACKAGING NET WEIGHT
0.21

PACKAGING WEIGHT UNIT
KGM