


Rocker with viewer for switch with pilot light for 1 element black Simon K45

REF. K115/14



BASIC INFORMATION

DESCRIPTION

Available in quarter and half module versions, the rocker with viewer and pilot light for 2-way switches of the Simon K45 collection, it is the perfect complement to give your 2-way switch a functional and sophisticated finish. With finishes in a stylish black colour, has a size of 45 x 22.5 mm and 10 mm depth that guarantees adapting the set in all types of spaces. Designed for installation both flush mounted and surface-mounted, it adapts to the needs of each room technical and aesthetics. Made of halogen-free thermoplastic, it protects the room in case of fire, which prevents the flame spread and toxicity by smoke; this material allows you to reach a temperature range of 5 more than 60 °C. 2 control mechanisms with rocker close can not be combined with adaptor plates of Simon Cima-Simon K45.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Rocker and installation manual

ETIM CLASS

EC000011

REMARKS

It is not possible to combine 2 narrow button control mechanisms on a Simon 500 Cima-Simon K45 adapter plate

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

AVAILABLE IN

Quarter and half module versions

KIT AVAILABILITY

No

NUMBER OF MODULES

Four

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

7021

INDICATOR FUNCTION

Yes

VERSION

Single

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.062

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

544320

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436047167

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

544320

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.62

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

72

PACKAGING NET WEIGHT

0.62

UNITARY PACKAGING GROSS
WEIGHT

0.062

PACKAGING WIDTH

72

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

105