Auxiliary cover for adapting K45 mini columns to floor trunking distribution baseboards stainless steel Simon Trunking

REF. **ALKA02/8**



BASIC INFORMATION

DESCRIPTION

Auxiliary cover to fit K45 mini columns to floor trunking distribution baseboards made of stainless steel, and belonging to the series Simon Trunking. Being made of stainless steel, it has a metallic finish, which is fully created for that adapts to any style of decoration, contributing to the spaces brightness and a touch modern. We recommend that, if you want to maintain this cover properly clean and shine, the cleaning will be done only with a soft and dry cloth that does not cause any type of scratching to the stainless steel, and it is also necessary to take into account the fact that you never be of clean with abrasive cloths or cleaners that you use chlorine in its formulation, as this may damage the material. It is a cover specially designed to adapt K45 mini columns on a distribution baseboard. If you use only the baseboard for the distribution of floor trunking, it is advisable to use the upper trim cover for distribution baseboard KTA904 / 8.

FINISH

Metal

MATERIAL

Stainless steel

COMPATIBILITY

Distribution sockets Simon Trunking

PACKAGING CONTENTS

Auxiliary cover to adapt K45 mini columns and installation manual

ETIM CLASS

EC002649

REMARKS

Specifically designed cover to adapt K45 mini columns on a distribution plinth. In the event of only using the distribution plinth for floor trunking, it is advisable to use the upper trim cover for the KTA904/8 distribution baseboard.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+120° C

EARTHING RESISTANCE
< 0.05 ?

ELECTRICAL PROPERTIES
With electrical continuity

HEAT RESISTANCE (°C)
+850°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
5 MOhms at 500 V.

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Using screws

INSTALLATION DIRECTION
Horizontal

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-2:2008

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436038042

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
422500

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.08

PRODUCT NET WEIGHT
0.08

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436038042

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
25

PACKAGING WIDTH
130

PACKAGING LENGTH
130

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
422500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.1

PACKAGING NET WEIGHT
0.08

PACKAGING WEIGHT UNIT
KGM