

Modular Luminaire 730 120x10 3000 K General DALI

REF. 73062340-883



BASIC INFORMATION

DESCRIPTION

For those that need quality lighting with great durability, we present the 730 modular luminaire with dimensions of 1195x100x75 mm. Its colour temperature is 3000K, which means that the tone of the light is warm.

The new modular luminaire 730 from Simon offers an efficiency of 99 lumens/W and a colour rendering index of 80, which makes it perfect for those who seek quality and functionality.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

No

LUMENS (LM)

3400 lm

IP RATING

IP44

DRIVER INCLUDED

Yes

LUMENS/W

3400lm/ 34,5W

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

L70 (°C)

100.000 h at 25°C

OPTICS

General

POWER SUPPLY (V~)

100/277 V~

L90 (°C)

50.000 h at 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

100°

POWER (W)

34.5 W

CONTROL

DALI

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

99 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted, Concealed ceiling, Semi-concealed ceiling, Flush-mounted

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053204412

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

3.1

PRODUCT NET WEIGHT

2.8

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053204412

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

87

PACKAGING WIDTH

110

PACKAGING LENGTH

1215

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

11627550

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

3.1

PACKAGING NET WEIGHT

2.8

PACKAGING WEIGHT UNIT

KGM