

People Counting Sensor 5x7m BT Mesh recessed box IP black IP20

REF. 89242521-238



BASIC INFORMATION

DESCRIPTION

Embedded people counting sensor. The recommended installation height is 2.8 m, with a maximum height of 3.5 m. It has a 360° detection angle. The detection and people counting range is 5 x 7 m. The device features brightness, temperature, and humidity sensors. The detector's configuration is done through a Bluetooth and IP application. The control protocol is IP. The power supply voltage is PoE Standard (IEEE 802.3 af). The operating temperature of the detector is: 0 - 40 °C. Black finish, IP 20 protection rating, and dimensions: 103 x 103 x 52 mm. 5-year warranty. For more product information, visit the STEINEL website by clicking [here](#).

FINISH

Black

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9005

POWER SUPPLY (V~)

Standard PoE (IEEE 802.3af)

CONTROL

IP

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2,5 m

INSTALLATION TYPE

Flush box mounting

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053430620

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.273

PRODUCT NET WEIGHT

0.144

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053430620

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.273

PACKAGING NET WEIGHT

0.144

PACKAGING WEIGHT UNIT

KGM