

Modular luminaire 720 Advance M4 60x60 Low Glare WW DALI

REF. 72060340-683



BASIC INFORMATION

DESCRIPTION

With interface of adjustment bidirectional DALI, the luminaire 720 Modular Advance M4 of the collection for indoor lighting of Simon, ensuring greater quality lighting adapted to any space, with the latest LED technology for an efficient energy savings. With a colour temperature of 3000K for a warm tone (WW), has optics micro prismatic system with anti-deslumbramiento LowGlare included. Its light flux of light 3200 lm / 28 W, it is compatible with 230 V AC Volts and 50-60 Hertz rate. Also, and thanks to its LED technology, has a service life of 100,000 hours for the L70 at 25 ° C and 40,000 hours for the L90. Its installation is suitable for both flush mounted and surface-mounted, it is designed for false ceiling and hardware that, together with its finishes in white, ensures integration of the set in all types of spaces, adapting to any style and ambience decorative.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

114 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Tipo 2

LUMENS (LM)

3200 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3200 lm/28W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Microprismatic

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

CONTROL

DALI

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053191750

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053191750

PACKAGING VOLUME

0.252

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

70

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

600

PACKAGING NET WEIGHT

5

UNITARY PACKAGING GROSS
WEIGHT

5.62

PACKAGING LENGTH

600

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

5