Variable external angle accessory for Cablomax trunking 170x55mm aluminum

REF. **TKA002213/8**



BASIC INFORMATION

DESCRIPTION

Cablomax aluminum channel accessory 170x55 mm. Adapts the channel to external bends between 65º and 95º between two planes. Manufactured with high-quality thermoplastic materials and in aluminum finish for proper integration with the channel.

FINISH

Aluminium

MATERIAL

Aluminium

ETIM CLASS

EC000872

REMARKS

The product installation can be supplemented with related accessories, as well as combined with K45 functions.

TECHNICAL INFORMATION

IK CLASSIFICATION
07

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

REMOVAL OF THE FRAME
Only with tool

INSTALLATION TYPE
On Wall and Ceiling

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436028500

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
1842750

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.15

PRODUCT NET WEIGHT
0.15

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436028500

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
63

PACKAGING WIDTH
130

PACKAGING LENGTH
225

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1842750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.15

PACKAGING NET WEIGHT
0.15

PACKAGING WEIGHT UNIT
KGM