

Back kit for 2 elements with 1 Schuko socket, 1 phase-cut dimmer switch 2/3 wires, and 1 USB charger 2.1A with smartcharge Simon 100

REF. 10010209-039



BASIC INFORMATION

DESCRIPTION

The objective of Simon is to simplify people. With this objective in mind, the 100 Series has prepared a multitude of mechanism kits to make installation more convenient and quicker: Mechanism kits, kits of outlets, data, image and audio. One of the best selling kits currently sold for use in both public and private buildings is the back kit for two elements with an IO Ready adjustable switch, a USB charger and a socket-outlet base included in this range. The main features that differentiates this pack from other similar products manufactured by the competition are: Intensity (USB: 2.1 A - Schuko: 16 A), voltage (230 V), terminal connection (Switch / USB: A screw - Schuko: By cutting of a click) and operation (Push-button rocker switch / Insertion), Its installation can be carried out simply in a few minutes in a universal box.

COMPATIBILITY

Front Kit Simon 100

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

POWER SUPPLY (V~)

250 V~

NUMBER OF POSSIBLE ELEMENTS

2 elements

TYPE OF MECHANISM

Push button rocker switch/Insertion

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

Schuko,USB

NOMINAL VOLTAGE (V~)

250 V~

USB CURRENT (A)

2,1 A

INDICATOR FUNCTION

Yes

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

USB VOLTAGE (V~)

5 Vdc

CURRENT (A)

16 A

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Horizontal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Schuko: 1 click connection (1 click®)

TYPE OF TERMINAL CONNECTION - FUNCTION 2

Switch/USB: Screw

INSTALLATION TYPE

Suitable for flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-1:2004 + EN 60669-2-1:2004 A1:2009 + EN 60669-2-1:2004 A12:2010*6 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2011*3 + ETSI-EN 301489-34 v14.1*3 + IEC 60884-1 Ed. 3.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053147818

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.268

PRODUCT NET WEIGHT

0.268

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053147818

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

75

PACKAGING WIDTH

88

PACKAGING LENGTH

158

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1042800

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

268.1

PACKAGING NET WEIGHT

0.268

PACKAGING WEIGHT UNIT

GRM