

MD-26 PIR+LUX BT Mesh surface On/Off anthracite IP54

REF. 89202136-140



BASIC INFORMATION

DESCRIPTION

Surface-mounted PIR motion and light-level detector. Recommended installation height is 2 m, with a maximum height of 6 m. It has a detection angle of 360°. The tangential detection range is 26 m and the radial detection range is 7 m.

The light-level adjustment range is 2 - 2000 lux and the timing range is 5 s - 60 min. The detector is configured via a Bluetooth app. It has a TEACH operating mode. Sensors can be interconnected via Bluetooth.

The control output is On/Off and the maximum switching power is 2000 W. Supply voltage is 220 - 240 VAC. Detector operating temperature: -20 - 40 °C. Anthracite finish, IP 54 protection rating and dimensions: Ø 80 x 93 mm. 5-year warranty.

For more product information, visit the STEINEL website by clicking [here](#)

FINISH

Anthracite

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

7016

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

1.8

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053462836

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.24

PRODUCT NET WEIGHT

0.17

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053462836

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

165

PACKAGING WIDTH

135

PACKAGING LENGTH

90

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2004750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.24

PACKAGING NET WEIGHT

0.17

PACKAGING WEIGHT UNIT

KGM