

Recessed movement and brightness detector 8m black IP54

REF. 89101112-138



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted motion and brightness detector. The recommended installation height is 2.5 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 8 m and the radial detection range is 4 m.

The brightness regulation range is 2 - 2000 lux and the timing range is 8 s - 35 min. The configuration of the detector is done through potentiometers.

The control output is On/Off and the maximum switchable power is 1000 W (64 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 40 °C.

Black finish, IP 54 protection rating, and dimensions: Ø 78 x 89 mm.

3-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

1000

RAL

9010

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION

HEIGHT

2.2

LOGISTICS INFORMATION

UNITARY EAN CODE	UNITARY PACKAGING GROSS WEIGHT	PACKAGING LENGTH
8421053369999	0.2	90
UNITARY PACKAGING HEIGHT	PRODUCT NET WEIGHT	PACKAGING MEASUREMENT UNIT
0	0.116	MMT
UNITARY PACKAGING WIDTH	UNITARY PACKAGING WEIGHT UNIT	PACKAGING VOLUME
0	KGM	2325323
UNITARY PACKAGING LENGTH	PACKAGING EAN	PACKAGING VOLUME UNIT
0	8421053369999	MMQ
UNITARY PACKAGING MEASUREMENT UNIT	UNITS CONTAINED PACKAGING	PACKAGING GROSS WEIGHT
MMT	1	0.2
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING NET WEIGHT
0	135	0.116
UNITARY PACKAGING VOLUME UNIT	PACKAGING WIDTH	PACKAGING WEIGHT UNIT
MMQ	90	KGM