

Movement detector relay switch 1000 W/VA 230V~ white Simon 82

REF. 82341-30



BASIC INFORMATION

FINISH

White

COMPATIBILITY

Simon 75, Simon 82 Detail,
Simon 82 Nature and Simon 82
frames

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

COMPATIBLE WITH MECHANICAL SWITCH

No

PACKAGING CONTENTS

Movement detector and
instruction sheet

ETIM CLASS

EC000133

REMARKS

Allows 5 units to be installed in parallel.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

NUMBER OF CONTACTS

3

NUMBER OF CONTROLLABLE CIRCUITS

1

DISCONNECTION TIMER

4 seconds to 10 minutes

COMPATIBLE WITH HALOGENS WITH ELECTRONIC TRANSFORMER (W)

VA

NUMBER OF POSSIBLE ELEMENTS

1 element

COMPATIBLE WITH FLUORESCENT LAMPS WITH 1-10V DIMMABLE ELECTRONIC BALLAST

No

COMPATIBLE WITH FLUORESCENT LAMPS (VA)

No

FREQUENCY

50 - 60 Hz

INDICATOR FUNCTION

Yes

IP RATING

IP20

COMPATIBLE WITH LOW CONSUMPTION (W)

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM QUANTITY PER CIRCUIT

5

TYPE OF MECHANISM

Detection

COMPATIBLE WITH MOTORS (VA)

No

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

POWER SUPPLY (V~)

230 V~

APPROXIMATE RANGE (M)

6 m

STORAGE TEMPERATURE RANGE (°C)

20 - 70 °C

VERSION

Single

NUMBER OF WIRES

2

INSTALLATION AND MAINTENANCE

BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

CABLE STRIPPING NECESSARY (MM)

8

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-2-1:2004 | EN 60669-2-1:2004 A1:2009 | EN 60669-2-1:2004 A12:2010 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053013120

PRODUCT NET WEIGHT

0.175

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

531200

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053013120

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.175

UNITARY PACKAGING VOLUME

531200

PACKAGING HEIGHT

81

PACKAGING NET WEIGHT

0.175

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING WIDTH

80

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS

WEIGHT

0.175

PACKAGING LENGTH

80