

Downlight 725.23 Flush mount WW General Aluminium

REF. 72523033-983



BASIC INFORMATION

DESCRIPTION

This Downlight is part of the range of lighting in indoor 725 of the brand Simon and is category A. The Downlight 725.23 Advance is equipped with a optics GENERAL that supplied warm light (WW) to any place where it is. It has a colour temperature of 3.100 k, 1200 lumens and 14 Watts, and requires a power supply of energy 100-240 flips and 50 / 60 Hertz rate of frequency. Its control system is very simple, consisting of the classic on / Off and its installation, it is also very easy to install, by means of recessed in walls and ceilings. This, together with its beautiful aluminium colour finish, make it to be well integrated in the ambience and decorative context of any place where it is placed, adding a touch of modernity to the room. In addition, according to the needs of lighting of the local or department where it is installed, you can combine with other downlights of the same features. Its measures are 165 x 51 millimetres, and is designed to be able to withstand very low and high temperatures ranging between - 15 and 40 degrees centigrade, without losing therefore nothing of functionality.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

1200 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 1

LUMENS/W

1200 lm/14W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3100 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

14 W

CONTROL

On/Off

COLOR TYPE

WW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

86 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

101

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.512

PRODUCT NET WEIGHT

0.512

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053116838

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

80

PACKAGING WIDTH

195

PACKAGING LENGTH

195

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.042

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.512

PACKAGING WEIGHT UNIT

KGM