

Complete kit with cover, brush, 3 schuko socket outlets and plate for 2 RJ45 connectors white S400 Indesk

REF. 44403020-130



BASIC INFORMATION

DESCRIPTION

Are you looking to access all the necessary connections quickly? This is now possible thanks to this complete table kit with cover and brush, which has the capacity for 3 schukos and a plate for 2 RJ45 connectors. A piece made of metal with a finish in aluminum from the cutting-edge Simon 400 Indesk series. A series created to be installed in any type of environment, offering solutions to the most demanding public at a very competitive price. Designed for a voltage of 250 volts and 16 amps of current, its dimensions are 250 x 185 x 85 millimeters and it features a manual lifting system for effective integration. All Simon products are made with top-quality materials, an example of which is the painted steel housing, the anodized aluminum profile, and the self-extinguishing halogen-free thermoplastic that this kit possesses.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

IK CLASSIFICATION

07

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

-5...+60

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9016

RECESS DIMENSION (MM)

228 x 175 mm (± 2mm)

NUMBER OF RJ45 WINDOWS

2

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

SNAP-FIT TYPE

Keystone I, II and Systimax

NUMBER OF SOCKETS

3 sockets for standard current circuit

VERSION

4 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45°

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053208151

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.85

PRODUCT NET WEIGHT

1.85

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053208151

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

275

PACKAGING WIDTH

195

PACKAGING LENGTH

90

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4826250

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.85

PACKAGING WEIGHT UNIT

KGM