

880.31 Industrial Spotlight 3000 K ASYM

REF. 88031038-273



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

111 lm/W

IK CLASSIFICATION

08

CRI

70

LUMENS (LM)

5550 lm

IP RATING

IP65

DIRECTIONAL

Yes

LUMENS/W

5550lm/ 50W

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

DRIVER INCLUDED

Yes

OPTICS

Asymmetric

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

30,000 h at 25 °C

POWER (W)

50 W

COLOR TYPE

WW

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface (with bracket)

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053205440

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.472

PRODUCT NET WEIGHT

2.287

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053205440

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

60

PACKAGING WIDTH

355

PACKAGING LENGTH

260

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

5538000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

2.472

PACKAGING NET WEIGHT

2.287

PACKAGING WEIGHT UNIT

KGM