

Accessory extensive ring 800.21

REF. 80091930-039



BASIC INFORMATION

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Units

ETIM CLASS

EC002557

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

SERVICE LIFE

50.000 h

IP RATING

IP54

PHOTOBIOLOGICAL CLASSIFICATION

Categoría exento

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Recessed

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50.000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053304631

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053304631

PACKAGING VOLUME

112500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

5

PACKAGING GROSS WEIGHT

0.072

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

150

PACKAGING NET WEIGHT

0.056

UNITARY PACKAGING GROSS WEIGHT

0.056

PACKAGING LENGTH

150

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.056