

Modular luminaire 720 Advance M4 60X60 WW CLC DALI

REF. 72060540-883



BASIC INFORMATION

DESCRIPTION

With translucent optics, interface of adjustment bidirectional DALI system and constant light control (CLC), the luminaire 720 modular Advance M4 of the collection Simon for indoor lighting, it is ideal to give the option to any room of the highest quality in lighting bonded greater savings. With a warm lighting to an ambience most welcoming, this luminaire has a luminous light flux 3200 lm for WW y a consumption of 28 W, compatible with a voltage of 230 V AC power and 50-60 Hz frequency. Thanks to having multiple LEDs, not only saves energy, but also has a service life of 40,000 hours at 25 ° C to L90 and up to 100,000 hours for the L70. With a perfect 60 x 60, its installation is designed for false ceiling, visible hardware, with the versatility of being able to be installed by flush mounted or surface-mounted. These features combined to its finishes in white tones tone, ensure the integration of the set in the space, providing a current and minimalist style.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

114 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Tipo 2

LUMENS (LM)

3200 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3200 lm/28W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Translucent

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

CONTROL

CLC,DALI

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.66

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053192184

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

70

PACKAGING WIDTH

600

PACKAGING LENGTH

600

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

25200000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

5

PACKAGING WEIGHT UNIT

KGM