Horizontal front kit for 2 elements with 1 German socket outlet, 1 rocker and 1 USB charger gloss white Simon 100

REF. **10021209-130**



BASIC INFORMATION

DESCRIPTION

Front kit to be installed horizontally designed to occupy 2 elements with 1 base Schuko type plug, 1 key and 1 USB charger. It is made in bright white and is part of the Simon 100 series.

Its installation is very simple and comfortable, just install the device horizontally. The type of connection is a switch and USB screw and in the case of the Schuko by cut (1 click®); it works with both push-button and by insert.

The material with which it is designed is prepared to reach temperatures that can oscillate, without any inconvenience, between 5 and 40º, and can end up supporting up to a maximum of -25 to 50º. For maintenance and cleaning, simply use a cloth dampened with soap and water, avoiding products containing chemical and abrasive materials.

It is based on regulations 2014/35 / UE LVD + directive 2014/30 / UE EMC + directive 2011/65 / UE RoHS + EN 50581: 2012 + EN 60669-2-1: 2004 + EN 60669-2- 1: 2004 A1: 2009 + EN 60669-2-1: 2004 A12: 2010 * 6 + EN 60950-1: 2006 + EN 60950-1: 2006 A11: 2009 + EN 60950-1: 2006 A1: 2010 + EN 60950 -1: 2006 A12: 2011 + EN 60950-1: 2006 A2: 2011 * 3 + ETSI-EN 301489-34 v14.1 * 3 + IEC 60884-1 Ed. 3.2 * 1.

FINISH

Gloss white

COMPATIBILITY

Kit mechanisms Simon 100

MATERIAL

Thermoplastic

ETIM CLASS

EC000007

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

NUMBER OF POSSIBLE ELEMENTS
2 elements

FORMAT
Schuko,USB

INDICATOR FUNCTION
Yes

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MONOBLOCK
Yes

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
2 elements

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION
Horizontal

INSTALLATION TYPE
Suitable for flush mounting

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-1:2004 + EN 60669-2-1:2004 A1:2009 + EN 60669-2-1:2004 A12:2010*6 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2011*3 + ETSI-EN 301489-34 v14.1*3 + IEC 60884-1 Ed. 3.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053147689

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.098

PRODUCT NET WEIGHT
0.098

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053147689

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
25.3

PACKAGING WIDTH
155

PACKAGING LENGTH
84

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
329406

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
98

PACKAGING NET WEIGHT
0.098

PACKAGING WEIGHT UNIT
GRM