simon

Console for lighting control Touch LightManager Advance graphite Simon Scena

REF. 89000110-038



BASIC INFORMATION

FINISH

Graphite

COMPATIBILITY

All types of luminaires and protocols

REMARKS

Requires flush-mount box ref 89000990-039.

PACKAGING CONTENTS

Touch LightManager, end-of-line resistor, frame holder and instructions

ETIM CLASS

EC000699



simon

TECHNICAL INFORMATION

BASIC CHARACTERISTICS

Allows scheduling and control of all system elements; version compatible with the Simon Scena App.

CIRCADIAN CYCLE

Yes

FREQUENCY (HZ)

50 - 60 Hz

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM NUMBER OF CHANNELS

512

TYPE OF MECHANISM

Touch screen, simple and userfriendly menu browsing

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

OPERATION

Programming and use

POWER CABLE SECTION (MM)

1.5 mm

POWER SUPPLY (V~)

100/230 V~

STORAGE TEMPERATURE RANGE (°C)

0 - 45 °C

USE

Fast and user-friendly with multiple interfaces, Touch LightManager display, App Simon Scena or optional keypad.

INSTALLATION AND MAINTENANCE

BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

CABLE CHARACTERISTICS DATA

Multicore AWG 24; 2 shielded twisted pairs with impedance of 120 Ohms

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific

INSTALLATION DIRECTION

Vertical

INSTALLATION TYPE

Semi-flush mount.

REGULATIONS



simon

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053125182

UNITARY PACKAGING GROSS

WEIGHT

0.61

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING LENGTH

0

PRODUCT NET WEIGHT

0.61

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053125182

PACKAGING GROSS WEIGHT

0

PACKAGING HEIGHT

77

PACKAGING LENGTH

251

PACKAGING NET WEIGHT

0.61

UNITS CONTAINED PACKAGING

1

PACKAGING MEASUREMENT

UNIT

MMT

PACKAGING VOLUME

2.947

PACKAGING VOLUME UNIT

DMQ

PACKAGING WEIGHT UNIT

KGM

PACKAGING WIDTH

196

