

Side cover with direct access 1 connector with 3 poles for
Ofiblock Compact-Line aluminium brackets light grey
Simon K45

REF. ACFC03/24



BASIC INFORMATION

DESCRIPTION

Achieve the perfect finish for its aluminium profile of Ofiblock Comapct-Line with the in light grey side cover with direct access for 1 connector, 3-pole. With a compact of 54 x 54 x 3 mm, this cover lateral integrates seamlessly into the set providing not only a current and minimalist design, but also to ensure greater efficiency and functionality for connectivity in your home or work area. It is manufactured in self-extinguishing thermoplastic and halogen-free that prevents the flame spread and toxicity by smoke in case of fire. Thanks to its manufacturing material, it can reach a temperature range of -5 more than 60 °C. Simon K45, gives the option of request supplied with machined according to the needs of the client and using order.

FINISH

Light grey

MATERIAL

Plastic

COMPATIBILITY

Ofiblocks Compact and Line
Simon K47

PACKAGING CONTENTS

Side cover with direct access for
1 3-pole quick connect connector

ETIM CLASS

EC000011

REMARKS

Can be supplied with machined parts depending on customer needs (upon request).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

HEAT RESISTANCE (°C)

+125°C (according to standard
IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP4X

KIT AVAILABILITY

Yes

LINKABLE

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

RAL

7035

NUMBER OF SIDE ENTRANCES

1

INSTALLATION AND MAINTENANCE

CABLING ACCESS

Through the housing fitted into the side cover.. Inlet for 3-pole quick connect connector.. Inlet for 3-pole quick connect connector.

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

PRODUCT NET WEIGHT
0.005

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING VOLUME
544.32

UNITARY PACKAGING LENGTH
0

PACKAGING EAN
8426436039148

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
544320

UNITS CONTAINED PACKAGING
20

PACKAGING GROSS WEIGHT
0.1

UNITARY PACKAGING VOLUME
UNIT
MMQ

PACKAGING HEIGHT
72

PACKAGING NET WEIGHT
0.1

UNITARY PACKAGING GROSS
WEIGHT
0.005

PACKAGING WIDTH
72

PACKAGING WEIGHT UNIT
KGM

PACKAGING LENGTH
105