

Spotlight 615 rail 3000 K Wide Flood white DALI

REF. 61500330-483



BASIC INFORMATION

APPLICATION

Accent lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

90

LIGHTING EFFICIENCY (LM/W)

80 lm/W

IP RATING

IP20

DIRECTIONAL

Yes

LUMENS (LM)

2000 lm

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

DRIVER INCLUDED

Yes

LUMENS/W

2000lm/ 25W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Wide Flood

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

50,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

DALI

COLOR TYPE

WW

POWER (W)

25 W

CHROMATICS CRI ICONS

CRI
90

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

3-phase adjustable rail

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053207215

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053207215

PACKAGING VOLUME

4400928

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

84

PACKAGING GROSS WEIGHT

0.846

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

177

PACKAGING NET WEIGHT

0.635

UNITARY PACKAGING GROSS
WEIGHT

0.846

PACKAGING LENGTH

296

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.635