


Mechanism-holder unit IP66 with safety lock for 1 function for 1 element brass Simon K45

REF. KSE0SEC/23/71



BASIC INFORMATION

DESCRIPTION

Element for fastening reference KSE0SEC / 23 / 71 of the range of products professional professionals, with Simon K45 Capacity for compatibilizar with other Products in the same range for different installations and environments. Work professionals. It is a unit holder Mechanisms unit with safety lock for a function of 1 element, Designed for situations flush-mounted into raised floor and flush mounted In concrete floors. Provides the maximum fastening and strength to different kinds of Systems and assemblies professionals. It measures 130 x 130 x 50 mm, it is made of metal with finishes in colour and colour, it is in brass An element dinamizador and versatil for Endorse all types of system.

FINISH

Brass

PACKAGING CONTENTS

Empty IP66 mechanism-holder unit with safety lock, square sealing gasket for IP66 tray, 4 screws for fastening the mechanism-holder unit and installation manual

ETIM CLASS

EC000024

MATERIAL

Metal

COMPATIBILITY

Simon K45 functions

REMARKS

The cover has anchor points that protect the connections during use against pressures and stresses due to the passage of personnel.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, when the mechanism-holder unit is not in use, the cover can be hermetically sealed.

AVAILABLE IN

Empty IP66 brass mechanism-holder unit to complete with solutions from the K45 range, with socket plug and housing for an RJ45 connector, and combination of a socket plug with RJ45 connector

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90° C

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

IK CLASSIFICATION

07,08

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP66

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1000kg

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 60° C

NUMBER OF MODULES

2 modules

RECESS DIMENSION (MM)

145 x 145 mm en falso suelo

VERSION

1 element

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF FASTENING

The mechanism-holder unit is fitted to the tray using 4 x 2.5 mm hexagonal head screws (Allen type) supplied with the mechanism-holder unit.

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plástica

INSTALLATION DIRECTION

The cover opens in the direction chosen according to the orientation of the tray during the installation phase.

INSTALLATION TYPE

Its design allows incorporation in any type of floor, be it a raised or a concrete floor, combining the mechanism-holder unit with the tray in accordance with the type of installation (ref. KGE170 for concrete floor, and ref. KGE170TF for raised floor)

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436043572

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

1445213

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.405

PRODUCT NET WEIGHT

0.405

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436043572

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

77

PACKAGING WIDTH

137

PACKAGING LENGTH

137

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1445213

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.405

PACKAGING NET WEIGHT

0.405

PACKAGING WEIGHT UNIT

KGM