

LedFlex 810.62 3000 K IP65 240 LED/m

REF. 81062100-983



BASIC INFORMATION

APPLICATION

General lighting, Indoor
decorative lighting

PACKAGING CONTENTS

1 unit (5m)

ETIM CLASS

EC002706

TECHNICAL INFORMATION

IP RATING

IP65

DRIVER INCLUDED

No

LUMENS (LM)

9100 lm

OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

L70 (°C)

30,000 h

LUMENS/W

9100 lm/70W

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

120°

OPTICS

General

CONTROL

PWM

COLOR TYPE

WW

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CRI

80

LIGHTING EFFICIENCY (LM/W)

130 lm/W

POWER (W)

70 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Hardware

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053203156

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.57

PRODUCT NET WEIGHT

0.45

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053203156

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

2

PACKAGING WIDTH

24

PACKAGING LENGTH

25

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1200

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.57

PACKAGING NET WEIGHT

0.45

PACKAGING WEIGHT UNIT

KGM