

Industrial luminaire 816.44 4000K GN

REF. 81644038-784



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

ETIM CLASS

EC001716

TECHNICAL INFORMATION

IK CLASSIFICATION

08

L70 (°C)

50.000 h at 25°C

OPTICS

General

IP RATING

IP65

LIGHT BEAM APERTURE ANGLE (°)

90°

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

4000 K

LIGHTING EFFICIENCY (LM/W)

128 lm/W

POWER (W)

240 W

CONTROL

DALI

LUMENS (LM)

30900 lm

SERVICE LIFE

50.000 h

CRI

80

LUMENS/W

30900 lm / 240W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Discontinued

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053229361

UNITARY PACKAGING HEIGHT

200

UNITARY PACKAGING WIDTH

485

UNITARY PACKAGING LENGTH

485

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

47045000

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

8

PRODUCT NET WEIGHT

6.6

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053229361

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

200

PACKAGING WIDTH

485

PACKAGING LENGTH

485

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

47045000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

8

PACKAGING NET WEIGHT

6.6

PACKAGING WEIGHT UNIT

KGM