

Kit Flash 90 consisting of schuko modular power socket, USB charger Type C 20W and housing for Keystone connector black Simon K45

REF. KR3310013/14



BASIC INFORMATION

DESCRIPTION

Kit Flash 90 based on a modular schuko power socket-outlet for installation in furniture with an optional protective lid to allow it to be closed and conceal the connections when not in use. Includes a 20W USB Type-C charger and a housing for a Keystone jack connector in black finish. Supplied with a 20cm long patch cable terminated with a 3-pole Wieland® Gst18i male quick-connector with a safety anchor to facilitate safe connection and disconnection from the mains without interrupting the power supply. The kit is supplied assembled with the internal connections pre-made. It is only necessary to cut the die in the furniture where the product will be mounted and, once completed, connect it to the mains for operation.

FINISH

Black

MATERIAL

Plastic

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Protective lid available (as an option) to protect the connections against entry of dust and small objects

RJ45 CONNECTORS

Yes

CONNECTOR TYPE

Schuko

NUMBER OF CONTACTS

3

DUST SHUTTER

No

FORMAT

Schuko

CURRENT (A)

16 A

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NOMINAL VOLTAGE (V~)

250 V~

RAL

9005

RECESS DIMENSION (MM)

ø80 mm

RJ45 ADAPTOR MODULE

Yes

SNAP-FIT RJ45 PLATES

Directly to the trim cover

SNAP-FIT TYPE

Keystone

USB CHARACTERISTICS

Charging

USB CURRENT (A)

2,2 A

POWER DELIVERY USB

Yes

QUICK CHARGE USB

Yes

USB VOLTAGE (V~)

9 V~

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

No tools needed

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD*1 | Dir. 2014/30/UE EMC*3 | Dir. 2011/65/UE RoHS + post. mod.*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) *1 *13 *12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012*2 | IEC 60884-1 Ed.3.2*1 | BS 1363-2:2016+A1:2018*2 | UNE 20315-1-1:2017*5 | BS 1363-4:2016+A1:2018*2 | UNE 20315-1-2:2017*5 | DS 60884-2-D1:2023*4 | CEI 23-50 V4*7 | SANS 164-1:2021*6 | SN 441011-2-1:2019*9 | SI 32 Fig. 204 B*8 | AS/NZS 3112:2017*11 | EN 50173-1:2018*10 | EN 50563:2011 + A1:2013*13 *12 | EN 55032:2015 + A11:2020 + A1:2020*12*14 *16 | EN 62368-1: 2014 + A11:2017*13 *12 | EN 55035:2017 + A11:2020*12*14 *16 | ETSI-EN 301489-34 V2.1.1*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024*12 *16 | EN IEC 60670-1:2021+ A11:2021*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 *12 *16 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053398081

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.578

PRODUCT NET WEIGHT

0.578

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053398081

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

120

PACKAGING WIDTH

130

PACKAGING LENGTH

252

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3931200

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.738

PACKAGING NET WEIGHT

0.578

PACKAGING WEIGHT UNIT

KGM