

Customisable set with 1 schuko socket outlet and 3 empty elements white S400 Top

REF. 42401000-130



BASIC INFORMATION

DESCRIPTION

With 1 Schuko socket-outlet and 3 empty elements, the kit of desk top customizable of Simon 400 Top, unify in a single mechanism their electrical devices and, optimising the space and getting functionality. With a compact design and finishes in a white tones tone, the kit is integrated into all types of spaces, providing a current of notes minimalist style. With an installation designed to be flush mounted on furniture, does not require additional tools, since it is done by already incorporated clamps. Connected to figure Wieland gst 18i, it is compatible with 250 Volt voltage and 16 Ampere current; it also has a insulation resistance > 5 M Ω at 500 V, and 2000 V at 50H / minute of dielectric strength. Made of anodised aluminium and self-extinguishing thermoplastic and halogen-free, prevents the flame spread and toxicity by smoke, in case of fire.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

NUMBER OF POSSIBLE ELEMENTS

3

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

NOMINAL VOLTAGE (V~)

250 V~

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9016

NUMBER OF REAR ENTRANCES

3

NUMBER OF SOCKETS

1 socket for standard current circuit

VERSION

4 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

REMOVAL OF COMPONENTS

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE

Suitable for fixing to furniture.

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053195598

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.82

PRODUCT NET WEIGHT

0.82

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053195598

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

240

PACKAGING WIDTH

125

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2850000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.82

PACKAGING WEIGHT UNIT

KGM