


Framework for 6 elements in adjustable floor box graphite Simon 500 Cima

REF. 52051803-038



BASIC INFORMATION

DESCRIPTION

With the elegance of Graphite, the framework for six elements of the collection Simon 500 Cima flush-mounted, is designed to be installed both in concrete or raised floor, thanks to the adjustable floor box, to suit every room and style. Manufactured with halogen-free thermoplastic materials, it guarantees the security of the no flame propagation and smoke poison in case of fire, reaching to reach a temperature range of -5 °C and 60 °C. Its design discreet, with finishes in stylish Graphite, it adds an innovative integrated design that each of its elements to the surface-mounted installation; provides security, thanks to the thermoplastic, and maximize the functionality. This makes the frame holder tandem mechanisms and adjustable floor box Simon 500 Cima, the decision perfect for combining style, security, innovation and functionality in a single space.

FINISH

Graphite

COMPATIBILITY

Simon 500 Cima and Simon 27
Play/Simon K45 mechanisms
(using a specific adaptor)

PACKAGING CONTENTS

Framework

MATERIAL

Plastic

ETIM CLASS

EC000007

REMARKS

The adjustable floor boxes include the framework in a white finish. It is recommended to combine this product with the graphite-finish adjustable floor boxes.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

HEAT RESISTANCE (°C)

+125°C (according rule IEC
60695-10-2)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

2, 4, 6 and 8 elements

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

NUMBER OF MODULES

6 modules

DIELECTRIC STRENGTH

No holes or contours, with 2000V
at 50 Hz for 1 minute

KIT AVAILABILITY

No

RAL

7021

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

VERSION

6 elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using screws

INSTALLATION DIRECTION

Horizontal, Vertical

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

In concrete floor and raised floor through the adjustable floor boxes

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053254844

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.065

PRODUCT NET WEIGHT

0.065

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053093313

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

100

PACKAGING WIDTH

135

PACKAGING LENGTH

347

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4684500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.65

PACKAGING WEIGHT UNIT

KGM

