

Trim cover for floor trunking distribution baseboards stainless steel Simon Trunking

REF. KTA904/8



BASIC INFORMATION

DESCRIPTION

Trim cover for floor trunking distribution baseboards made of stainless steel and that belongs to the series of Simon Trunking. This cover has dimensions of 140 x 140 x 3 mm This is especially designed to distribute the floor trunking. In the case you need adapt it to K45 mini columns taking advantage of the installation of the distribution baseboard, it is advisable to use the cover adapter ALKA02 / 8. Simon Trunking consists of a series of products designed fully adapted to the new trends in the decoration of spaces, maintaining a high degree of aesthetic integration. Therefore, it consists of a fully finish, a metal finish, very used in the market today and that every time it is used in the world of decoration for the brightness and colour that gives the spaces. If you want to keep this trim cover clean and in perfect condition you only need to wipe it with a soft and dry cloth, taking into account that you must never use abrasive cloths or cleaners containing chlorine in their formulation as it could get damaged.

FINISH

Metal

MATERIAL

Stainless steel

COMPATIBILITY

Distribution sockets Simon Trunking

PACKAGING CONTENTS

Trim cover for floor trunking distribution baseboards, ground connection cable, screws and installation manual

ETIM CLASS

EC002417

REMARKS

Specifically designed cover for distributing floor trunking. In the event of needing to adapt K45 mini columns taking advantage of the distribution baseboard installation, it is recommended to use the ALKA02/8 adaptor cover.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

Without perforation or
contournement with 2000 V at
50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

HEAT RESISTANCE (°C)

+850°C (according rule IEC
60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using supplied screws

INSTALLATION DIRECTION

Horizontal

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-2:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436035447

PRODUCT NET WEIGHT

0.105

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

422500

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436035447

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.105

UNITARY PACKAGING VOLUME

422500

PACKAGING HEIGHT

25

PACKAGING NET WEIGHT

0.105

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

130

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.105

PACKAGING LENGTH

130