


Ledline 815 NW 1200 mm

REF. 81531033-984



BASIC INFORMATION

APPLICATION

Ambient lighting, Alcove
lighting, Furniture lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC000282

REMARKS

Luminaires for interconnecting up to a maximum of 150W

TECHNICAL INFORMATION

FREQUENCY (HZ)

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

1500 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 1

LUMENS/W

1500 lm/18W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

230 V~

L70 (°C)

35,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3900 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

18 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

84 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING GROSS WEIGHT

0.388

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING LENGTH

0

PRODUCT NET WEIGHT

0.388

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053122440

PACKAGING GROSS WEIGHT

0.388

PACKAGING HEIGHT

25

PACKAGING LENGTH

670

PACKAGING NET WEIGHT

0.388

UNITS CONTAINED PACKAGING

1

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.586

PACKAGING VOLUME UNIT

DMQ

PACKAGING WEIGHT UNIT

KGM

PACKAGING WIDTH

35