

Bipolar thermal-magnetic 16A with double element trim plate and 32 mm height white Simon Cima

REF. SMAS/9



BASIC INFORMATION

FINISH

White

COMPATIBILITY

With Cima Classic surface-mount boxes, Cima Classic flush-mount boxes with a 60mm housing, Cima towers and Cima columns and mini columns.

ETIM CLASS

EC000042

TECHNICAL INFORMATION

BREAKING CAPACITY (A)

6000 A

KIT AVAILABILITY

No

POWER SUPPLY (V~)

400 V~

CURRENT (A)

16 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

9003

IP RATING

IP20

TRIP CURVE

C Curve

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

10

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REMOVAL OF THE MCB

Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436043121

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

753878

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.345

PRODUCT NET WEIGHT

0.345

UNITARY PACKAGING WEIGHT UNIT

KGM

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

118

PACKAGING WIDTH

121

PACKAGING LENGTH

264

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3769392

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.725

PACKAGING NET WEIGHT

1.725

PACKAGING WEIGHT UNIT

KGM