# Voice and data flat plate for 1 element without dust cover for 1 R&M® RJ45 connector black Simon K45

REF. **K054/14**



# BASIC INFORMATION

## DESCRIPTION

Voice and data flat plate without dust shutter. This plate is of the series Simon K45 and has an element for an RJ45 connector from R & M The product commitment to a stylish finished in black colour. It is grey, specifically, the individual version half module, its installation you can perform either in surface-mounted and flush mounted. If you want to combine this plate of voice and data Simon in any type of enclosure vertical, as mini-columns, channels portacaminos or Teleblock, it is essential to use the 90 ° positioner (reference: K66), in order to guide the plate into a vertical position. The dimensions of the plate are 45 x 45 millimetres, with a depth of 8.5 millimetres. It is made of a thermoplastic material, free of any type of halogen, guaranteeing no flame spread in case of fire management, as well as the minimum toxicity in case of smoke thanks to these materials of as high quality, the plate can withstand temperatures of up to + 60 degrees centigrade.

## FINISH

Black

## COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

## PACKAGING CONTENTS

Flat voice and data plate without dust cover

## ETIM CLASS

EC000018

## REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### COMPATIBLE WITH CONNECTORS
R&M® (Reichle de Massari®).Classic Series Cat5e (R925371, R925370) and Star Series Cat6 (R302373, R302372).

### RJ45 CONNECTORS
Not included in voice and data plate

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

### DUST PROTECTION
No

### FORMAT
RJ45

### IP RATING
IP20

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

### NUMBER OF MODULES
Half

### PLATE TYPE
Flat

### RAL
7021

### RJ45 ADAPTOR MODULE
Included in voice and data plate

### SNAP-FIT RJ45 PLATES
R&M® RJ45 connectors

### SNAP-FIT TYPE
R&M® RJ45 connectors

### VERSION
Single

## INSTALLATION AND MAINTENANCE

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

### INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

### INSTALLATION TYPE
Suitable for surface and flush mounting

### REMOVAL OF THE PLATE
Only with tool

## REGULATIONS

### REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.011

PRODUCT NET WEIGHT
0.011

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436046917

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
88

PACKAGING WIDTH
123

PACKAGING LENGTH
136

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1472064

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.22

PACKAGING NET WEIGHT
0.22

PACKAGING WEIGHT UNIT
KGM