
RF receiver mechanism, switch/push button (allows up to 15 transmitters 75888-39)

REF. **75887-39**



BASIC INFORMATION

DESCRIPTION

Technology is very present in the mechanisms that make up the different elements of our homes and businesses. A good example of this is the medium-element receiver Radio Frequency of switch - push-button switch of the Simon 82 series, this device allows individual and / or centralized command from one to fifteen emitting points. It also uses the latest technology (interface 868 Mhz) ensuring reliability, good operation and excellent reception level, without interference when passing the signal through the walls. It can be used as load power: Incandescent and halogen 230V 2600W, halogen with electromagnetic transformer 650VA, halogen with electric transformer 550 Hz, balanced fluorescence without resistance 600VA, unbalanced fluorescence 1500VA, electronic fluorescence 520VA, Dulux 250 VA lamp and 1500VA motors. It can also be installed in a universal box, register box, hollow partition wall or false ceiling. Its power is 230V~ and it has been manufactured with the best electronic components with halogen-free thermoplastic insulation.

COMPATIBILITY

Simon 75, Simon 82 Detail, Simon 82 Nature and Simon 82 frames

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

COMPATIBLE WITH MECHANICAL SWITCH

No

PACKAGING CONTENTS

RF receiver switch/press button and instruction sheet

REMARKS

Supplied in 2-way switch mode.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 1,5 to 2,5 mm

NUMBER OF CONTACTS
3

NUMBER OF CONTROLLABLE CIRCUITS
1

COMPATIBLE WITH ELECTRONIC AUXILIARY
No

COMPATIBLE WITH FLUORESCENT LAMPS (VA)
600 VA Compensated, no resistance

FREQUENCY
50 - 60 Hz

IP RATING
IP20

COMPATIBLE WITH LOW CONSUMPTION (W)
No

COMPATIBLE WITH MOTORS (VA)
1500 VA

OPERATING TEMPERATURE RANGE (°C)
0 - 55 °C

POWER SUPPLY (V~)
230 V~

NUMBER OF WIRES
3

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
8

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + Directive 2014/53/UE RED + EN 50364:2010 + EN 50581:2012 + EN 60669-2-1:2004 + EN 60669-2-1:2004 A1:2009 + EN 60669-2-1:2004 A12:2010 + ETSI EN 300 330 V2.1.1. + ETSI EN 301 489-3 V2.1.1.

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053069370

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
329232

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.08

PRODUCT NET WEIGHT
0.08

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053069370

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
57

PACKAGING WIDTH
76

PACKAGING LENGTH
76

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.329

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.085

PACKAGING NET WEIGHT
0.08

PACKAGING WEIGHT UNIT
KGM