Projector 889 20W 4000K

REF. **88931038-884**



BASIC INFORMATION

DESCRIPTION

Outdoor LED projector for showcase and facade lighting, robust, adjustable and designed for high performance in commercial applications. Available in different power ratings, the outdoor projector 889 allows you to select the appropriate model according to the mounting height, the surface to be illuminated, and the desired impact level. Installation type: Surface. Optics: 110. Color temperature: 4000K. Power: 20W. Lumens: 1600lm. Efficiency: 80lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 127 mm x 107 mm x 28 mm.

APPLICATION

Wall lighting,Industrial lighting,Commercial areas

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IK CLASSIFICATION
05

IP RATING
IP65

OPERATING TEMPERATURE RANGE (°C)
-25...+50

POWER SUPPLY (V~)
220/240 V~

CONTROL
On/Off

LIGHTING EFFICIENCY (LM/W)
80 lm/W

LUMENS (LM)
1600 lm

OPTICS
Symmetric

POWER (W)
20 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053440513

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.209

PRODUCT NET WEIGHT
0.188

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053440513

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
250

PACKAGING WIDTH
190

PACKAGING LENGTH
285

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
13537500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
4.18

PACKAGING NET WEIGHT
0.188

PACKAGING WEIGHT UNIT
KGM