

PD-6x6 Micro PIR+LUX recessed KNX white IP65

REF. 89219711-130



BASIC INFORMATION

DESCRIPTION

PIR presence and brightness detector for flush mounting. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 90°. The tangential detection range is 6 x 6 m and the radial detection range is 4 x 4 m.

The brightness regulation range is 2 - 1000 lux and the timing range is 1 min - 255 min. The configuration of the detector is done through potentiometers and KNX.

It features a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 10 mA.

The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -25 - 55°C.

White finish, IP 65 protection rating, and dimensions: Ø 43 x 75 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP65

RAL

9003

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053343203

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.093

PRODUCT NET WEIGHT

0.03

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053343203

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

120

PACKAGING WIDTH

75

PACKAGING LENGTH

90

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

810000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.093

PACKAGING NET WEIGHT

0.03

PACKAGING WEIGHT UNIT

KGM