

**Complete kit with dual opening cover, brush, 6 schuko
socket outlets and plate for 4 RJ45 connectors white S400
Indesk Duo**

REF. 46403020-130



BASIC INFORMATION

DESCRIPTION

Among the flush-mounted devices in the Simon 400 Indesk Duo series, the kit integrated into the table stands out, complete with a cover featuring two openings and a brush, six schuko socket bases for standard power circuit, and plates for four RJ45 connectors in white. Insulation resistance of >5 MO at 500 V, intensity of 16 A, Wieland® gst18i connector with three male aerial poles with a 22 cm patch cord, voltage of 250 V~ and dielectric strength without perforation or contouring with 2000 V at 50 Hz for 1 minute are other features. Why is this kit so resistant and safe? Due to the painted steel casing, anodized aluminum profile, covers, and fasteners made of self-extinguishing thermoplastic free of halogens, with which its structure has been manufactured, materials that ensure no flame propagation in the event of a fire and low toxicity in case of smoke emission.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

RAL

9016

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

CURRENT (A)

16 A

RECESS DIMENSION (MM)

228 x 175 mm (± 2mm)

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

IP RATING

IP30

NUMBER OF RJ45 WINDOWS

4

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

SNAP-FIT TYPE

Keystone I, II and Systimax

FORMAT

Schuko

NOMINAL VOLTAGE (V~)

250 V~

NUMBER OF SOCKETS

6 sockets for standard current circuit

VERSION

8 elements

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45° and 135°

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053208519

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.35

PRODUCT NET WEIGHT

2.35

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053208519

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

370

PACKAGING WIDTH

135

PACKAGING LENGTH

200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9990000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.35

PACKAGING WEIGHT UNIT

KGM