

RF receiver mechanism, switch/push button (allows up to 15 transmitters 75888-39)

REF. 75887-39



BASIC INFORMATION

DESCRIPTION

Technology is very present in the mechanisms that make up the different elements of our homes and businesses. A good example of this is the medium-element receiver Radio Frequency of switch - push-button switch of the Simon 82 series, this device allows individual and / or centralized command from one to fifteen emitting points. It also uses the latest technology (interface 868 Mhz) ensuring reliability, good operation and excellent reception level, without interference when passing the signal through the walls. It can be used as load power: Incandescent and halogen 230V 2600W, halogen with electromagnetic transformer 650VA, halogen with electric transformer 550 Hz, balanced fluorescence without resistance 600VA, unbalanced fluorescence 1500VA, electronic fluorescence 520VA, Dulux 250 VA lamp and 1500VA motors. It can also be installed in a universal box, register box, hollow partition wall or false ceiling. Its power is 230V~ and it has been manufactured with the best electronic components with halogen-free thermoplastic insulation.

COMPATIBILITY

Simon 75, Simon 82 Detail,
Simon 82 Nature and Simon 82
frames

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

COMPATIBLE WITH MECHANICAL SWITCH

No

PACKAGING CONTENTS

RF receiver switch/press button
and instruction sheet

REMARKS

Supplied in 2-way switch mode.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

NUMBER OF CONTACTS

3

NUMBER OF CONTROLLABLE CIRCUITS

1

COMPATIBLE WITH ELECTRONIC AUXILIARY

No

COMPATIBLE WITH FLUORESCENT LAMPS (VA)

600 VA Compensated, no resistance

FREQUENCY

50 - 60 Hz

IP RATING

IP20

COMPATIBLE WITH LOW CONSUMPTION (W)

No

COMPATIBLE WITH MOTORS (VA)

1500 VA

OPERATING TEMPERATURE RANGE (°C)

0 - 55 °C

POWER SUPPLY (V~)

230 V~

NUMBER OF WIRES

3

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

8

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + Directive 2014/53/UE RED + EN 50364:2010 + EN 50581:2012 + EN 60669-2-1:2004 + EN 60669-2-1:2004 A1:2009 + EN 60669-2-1:2004 A12:2010 + ETSI EN 300 330 V2.1.1. + ETSI EN 301 489-3 V2.1.1.

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053069370

PRODUCT NET WEIGHT

0.08

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0.329

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053069370

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.085

UNITARY PACKAGING VOLUME

329232

PACKAGING HEIGHT

57

PACKAGING NET WEIGHT

0.08

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

76

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.08

PACKAGING LENGTH

76