Kit Flash 60 consisting of schuko power socket end in Quick-connection connector black Simon 400

REF. **43101002-138**



BASIC INFORMATION

DESCRIPTION

Kit based on schuko socket-outlet to be installed in furniture with an optional protective cover to allow for closure and conceal connections when not in use. This product is supplied in black finish, assembled and wired with a 20 cm long flexible cable ending in a male quick connect overhead connector of 3 poles type Wieland® GST8i with safety anchoring to facilitate safe connection and disconnection from the power network without the need to interrupt the power supply. The kit is supplied with the internal connections already made. It is only necessary to create the hole in the furniture where the product will be fasten and once done, connect it to the power supply to make it functional.

FINISH	MATERIAL	ETIM CLASS
Black	Plastic	EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
Yes

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Protective lid available (as an option) to protect the socket-outlet against entry of dust and small objects

RJ45 CONNECTORS
No

CONNECTOR TYPE
Schuko

NUMBER OF CONTACTS
3

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

CURRENT (A)
16 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NOMINAL VOLTAGE (V~)
250 V~

RAL
9005

RECESS DIMENSION (MM)
ø54 mm

RJ45 ADAPTOR MODULE
No

SNAP-FIT RJ45 PLATES
No

SNAP-FIT TYPE
No

VOLTAGE (V~)
250 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF CONNECTOR
No tools needed

EXTINGUISHING (°C)
+650 °C (according to standard IEC 60670)

REMOVAL OF THE FRAME
Only with tool

SECURING POSSIBILITIES
Using supplied claws

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Quick connector

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | IEC 60884-2-7 Ed 1.1*1 | UNE 20315-2-7:2008*1 | EN IEC 63000:2018 | IEC 60884-1 Ed 3.2*2 | UNE 20315-1-1:2017*2

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053292099

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.136

PRODUCT NET WEIGHT
0.124

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053292099

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
72

PACKAGING WIDTH
72

PACKAGING LENGTH
105

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
544320

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.136

PACKAGING NET WEIGHT
0.124

PACKAGING WEIGHT UNIT
KGM