

Voice and data flat plate with dust cover for 1 element and 2 RJ45 connectors category 5e FTP black Simon K45

REF. KB95F/14



BASIC INFORMATION

DESCRIPTION

The best ally to protect the electronic systems is the flat plate for voice and data with dust cover for an element and 2 RJ45 category 5e FTP connectors in black colour of the series Simon K45 resistant, durable and functional, it is ideal to decorate any type of space, this piece has dimensions of 45 x 45 x 42 ' 9 mm It has a cabling 22-24 AWG, is suitable for surface-mounted and recess and its structure has been manufactured with metal components with self-extinguishing thermoplastic insulation and halogen. Thanks to this material we safe against any fire, as this component guarantees no flame propagation in case of fire and the low toxicity in case of smoke with insertion tool, in case of combining with mini columns, columns, Teleblock, channels, mechanism holders) you must use the 90° positioner (reference K66) to guide the plate into a vertical position.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Voice and data flat plate with dust cover, RJ45 category 5e FTP connectors and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING

CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

NUMBER OF MODULES

Half

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.045

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

3769392

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436042520

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.45

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

118

PACKAGING NET WEIGHT

0.45

UNITARY PACKAGING GROSS WEIGHT

0.045

PACKAGING WIDTH

121

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

264