

PD-40 Large Areas PIR+LUX SR surface DALI-2 Master squared white IP54

REF. 89218439-230



BASIC INFORMATION

DESCRIPTION

Surface PIR presence and light detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 40 m and the radial detection range is 8 m.

The light regulation range is 2 - 1000 lux and the timing range is 5 s - 15 min. The configuration of the detector is done via potentiometers and remote control.

It features a TEACH operating mode. Possibility of interconnection between sensors via DALI. The control protocol is DALI-2 Master. The number of dimmable luminaires via the DALI bus is 30 (1 group).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C. White finish, protection rating IP 54, and dimensions: 95 x 95 x 65 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2 Master

IP RATING

IP54

RAL

9003

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342985

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.253

PRODUCT NET WEIGHT

0.164

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342985

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1785600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.253

PACKAGING NET WEIGHT

0.164

PACKAGING WEIGHT UNIT

KGM