

S-Video connector female with trim plate white Simon K45

REF. K103B/9



BASIC INFORMATION

DESCRIPTION

The K45 series of Simon is composed of all types of products designed to the interconnectivity in professional environments such as offices, meeting rooms or even hospitals and libraries. So you require multiple mechanism to give solution to the different types of connections that exist today. Such as this S-Video connector, half an element. With trim plate in white colour, it is made of metal components with thermoplastic insulation of high range and halogen-free. It is fireproof, self-extinguishing. In this way, Simon ensures that the is not propagate fire and the low toxicity in case of smoke will be of fire. This socket is available both to be recessed and surface-mounted, it has a screw terminal connection, without the need for welding and has a section from 0.2 to 0.5 mm cable section. It is recommended not to use a cabling greater than 30 meters.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Female S-Video connector, wire cable tie and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 30 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

S-Video

RAL

9003

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

CONNECTOR TYPE

S-Video

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

NUMBER OF CONTACTS

4

NUMBER OF WIRES

5

NUMBER OF POSSIBLE ELEMENTS

1/2 element

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436064690

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436064690

PACKAGING VOLUME

0.012

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

50

PACKAGING GROSS WEIGHT

0.025

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

42

PACKAGING NET WEIGHT

0.023

UNITARY PACKAGING GROSS
WEIGHT

0.025

PACKAGING LENGTH

50

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.023