

Flat voice and data plate with dust cover for 1 element with 1 RJ45 category 6 FTP graphite Simon 500 Cima

REF. 50003085-038



BASIC INFORMATION

DESCRIPTION

Voice and data flat plate with dust shutter, of the Simon 500 Cima series. It incorporates a single element, with an RJ45 connector, it is a product category 6 FTP, graphite grey finish. It has a module and is part of the individual version of the series. It is available, in addition, both for one and two connectors. It is manufactured with metallic components isolated from thermoplastic, which minimizes the flame spread in case of fire. Also, the voice and data plates of this series, does not contain halogens, guaranteeing the lower toxicity in case of smoke. With measures of 50 x 50 mm and 45,4 mm depth, the voice and data plates Simon 500 Cima, incorporate the clips necessary to be able to be fixed in any type of enclosure, both vertically and horizontally. It is, therefore, one of the most versatile and functional on the market and maintenance is simple.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 6 FTP RJ45 connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Flat

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
170

UNITARY PACKAGING WIDTH
165

UNITARY PACKAGING LENGTH
200

UNITARY PACKAGING
MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
5610000

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.036

PRODUCT NET WEIGHT
0.036

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053098028

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
112

PACKAGING WIDTH
117

PACKAGING LENGTH
269

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
0.052

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.72

PACKAGING WEIGHT UNIT
KGM

