

Custom button box 4 functions for lighting control in homes and hotels graphite Simon 82 Sense

REF. 8000643-038



BASIC INFORMATION

FINISH

Graphite

PACKAGING CONTENTS

Keypad and instructions

MATERIAL

Thermoplastic

ETIM CLASS

EC000205

REMARKS

Requires installation on LON or KNX bus coupling unit (8000100-039 or 8400100-039). Possibility of customising and creating your own configuration by choosing the functions you need from our icon library.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

NUMBER OF POSSIBLE ELEMENTS

1 element

INDICATOR FUNCTION

Yes

CURRENT (A)

8 mA

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Touch

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

POWER SUPPLY (V~)

24 Vdc

RELATIVE HUMIDITY

From 20 to 85% (without condensation)

SLIDE CONTROL

No

SOUND FEEDBACK

Yes

STORAGE TEMPERATURE RANGE (°C)

25 - 70 °C

VIBRATION FEEDBACK

Yes

INSTALLATION AND MAINTENANCE

BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-5:2016

LOGISTICS INFORMATION

UNITARY EAN CODE 8421053128701	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING HEIGHT 0	PACKAGING EAN 8421053128701	PACKAGING VOLUME 129.688
UNITARY PACKAGING WIDTH 0	UNITS CONTAINED PACKAGING 1	PACKAGING VOLUME UNIT CMQ
UNITARY PACKAGING LENGTH 0	PACKAGING HEIGHT 26	PACKAGING GROSS WEIGHT 0
UNITARY PACKAGING VOLUME 0	PACKAGING WIDTH 58	PACKAGING NET WEIGHT 0.033
UNITARY PACKAGING GROSS WEIGHT 0.033	PACKAGING LENGTH 86	PACKAGING WEIGHT UNIT KGM
PRODUCT NET WEIGHT 0.033		