

Charger 5V DC using USB port type A white Simon K45

REF. K126B/9



BASIC INFORMATION

DESCRIPTION

Model charger K126B / 9 5V / DC socket outlet of the series Simon K45 format USB type A, is compatible for all types of environments. Installation system simple and simple with type of screw terminal connection, colour and finishes in colour bank. Element charger in USB format designed for electrical systems that offer values of intensity of 1.5 A and a voltage of limit of about 230 Volts, individual version with capacity for 2 modules, manufactured with metal components with halogen-free insulation, ensuring security and protection Of certified professionally. It measures 45 x 45mm and a measure of depth of 43mm ideal to form part active on all types of surfaces and installations. It offers a assembly and anchoring firm and safe, an option versatile for different outlets, providing a connection comfortable and quicker, giving the highest levels of security and protection professionally.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

USB charger, trim cover and installation manual

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

1,5 A

TYPE OF MECHANISM

Insertion

CABLE SECTION ADMITTED (MM)

From 1,0 to 2,5 mm

IP RATING

IP20

NUMBER OF MODULES

2 modules

NUMBER OF CONNECTIONS PER TERMINAL

1 connection per terminal

KIT AVAILABILITY

No

MONOBLOCK

No

MAX TEMP DURING CONSTRUCTION WORK (°C)

0 a 45° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

9003

FORMAT

USB

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to 50° C

VERSION

Single

VOLTAGE (V~)

230 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

6

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

REMOVAL OF THE SOCKET

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor ref.50012088-030

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

NUMBER OF TERMINALS

2 inputs

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2013 + ETSI-EN 301489-34 V1.4.1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT	PACKAGING MEASUREMENT
0	UNIT	UNIT
	KGM	MMT
UNITARY PACKAGING WIDTH		
0	PACKAGING EAN	PACKAGING VOLUME
	8421053134344	329232
UNITARY PACKAGING LENGTH		
0	UNITS CONTAINED PACKAGING	PACKAGING VOLUME UNIT
	1	MMQ
UNITARY PACKAGING VOLUME		
0	PACKAGING HEIGHT	PACKAGING GROSS WEIGHT
	57	0.045
UNITARY PACKAGING GROSS WEIGHT		
0.045	PACKAGING WIDTH	PACKAGING NET WEIGHT
	76	0.045
PRODUCT NET WEIGHT		
0.045	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
	76	KGM