

2-way switch for card with 1 micro switch and light indicator 250V~ aluminium Simon 75

REF. 75526-33



BASIC INFORMATION

DESCRIPTION

This Simon 75 series includes multiple options of design, thanks to all the combinations of colours (different finishes for rockers, parts pieces and frames) and also of shapes, as it has a rectangular design that adapts to two different shapes. A 2-way switch is a switch that the 2-way switch, each time a detached circuit, connected to another. That ' s why for Simon are all important. This 2-way switch for card with 1 microswitch and indicator light (its code is the 75526-33) resists elements up to 6 Amps and 250 Volt. Its finish is in aluminium. As far as its installation is concerned, we recommend that you do in combination with a contactor / relay. If not makes this way, remember that the maximum current of the 2-way switch is 6 Amps (2nd inductive). In terms of the installation of the frame, remember to break the flanges.

FINISH

Aluminium

COMPATIBILITY

Simon 75 frames

PACKAGING CONTENTS

Mechanism and cover

REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connectors with a heat shrink sleeve.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	INDICATOR FUNCTION Yes	NOMINAL VOLTAGE (V~) 250 V~
CABLE SECTION ADMITTED (MM) 0,5 mm	CURRENT (A) 10 (1,5 ind.) A	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
CONSUMPTION INDICATOR (MA) 1 mA	IP RATING IP20	POWER SUPPLY (V~) 250 V~
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
FREQUENCY 50 Hz	TYPE OF MECHANISM Card	VERSION Single

INSTALLATION AND MAINTENANCE

CLAW Simon 27	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Faston
INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	INSTALLATION TYPE Suitable for surface and flush mounting	

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
1517738

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.075

PRODUCT NET WEIGHT
0.075

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053017951

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
82

PACKAGING WIDTH
83

PACKAGING LENGTH
223

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
3017190

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.375

PACKAGING NET WEIGHT
0.375

PACKAGING WEIGHT UNIT
KGM