

Basic metallic IP40 and IK10 box 2 German outlets with keys, combined auto.differential circ. breaker 16A and programmable timer

REF. 0602122-039



BASIC INFORMATION

FINISH

Aluminium

COMPATIBILITY

Simon 500 CIMA mechanisms

PACKAGING CONTENTS

Box and instruction sheet

APPLICATION

Residential

OPERATING ENVIRONMENT

Residential

ETIM CLASS

EC002883

REMARKS

Tests have been carried out with the German connector (EEC 7/4) to guarantee a charge of 8 hours a day with an intensity of 16A.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 A

OPERATION OF THE OUTLET(S)

Simultaneous

CABLE SECTION ADMITTED (MM)

2,5 to 6 mm

IP RATING

IP40

POWER RANGE (KW)

3.6 kW

TYPE OF CONNECTION

External (via protected terminal connections)

TYPE OF LINE

Single-phase

TYPE OF PROTECTION

Magnetothermal differential, overcurrent and short circuits

ELECTRICITY METER

No

OPERATING TEMPERATURE RANGE (°C)

-20 - 60 °C

STORAGE TEMPERATURE RANGE (°C)

25 - 70 °C

EMERGENCY STOP

No

OTHER FEATURES

Con acceso por tapa + llave; Sin medidor de energía; Con protección eléctrica; Con programación horaria

TIME PROGRAMMING

Yes

FREQUENCY

50 Hz

TOLERANCE (%)

10

IK CLASSIFICATION

10

NUMBER OF OUTLETS

2

INSTALLATION AND MAINTENANCE

DISASSEMBLY REQUIRED

0

INSTALLATION TYPE

Suitable for surface mounting (4 bolts)

REGULATIONS

EV READY CERTIFICATION

No

ZE READY CERTIFICATION

No

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053129715

PACKAGING VOLUME

8854586

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

134

PACKAGING GROSS WEIGHT

3.5

UNITARY PACKAGING GROSS WEIGHT

3.05

PACKAGING WIDTH

221

PACKAGING NET WEIGHT

3.05

PRODUCT NET WEIGHT

3.05

PACKAGING LENGTH

299

PACKAGING WEIGHT UNIT

KGM