

Kit 2 LOOP Wall-mounted luminaires + 1 driver On/Off White

REF. 91229954B300



BASIC INFORMATION

BODY MATERIAL

Die-cast aluminium

APPLICATION

Domestic, Office, Retail, Hotel, Contract

PACKAGING CONTENTS

2 Unites

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

COLOR TYPE

NW

IP RATING

IP20

DIRECTIONAL

Yes

LIGHTING EFFICIENCY (LM/W)

hasta 26 lm/W

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

DRIVER INCLUDED

Yes

LUMENS (LM)

154 lm

POWER SUPPLY (V~)

110/240 V~

ELECTRICAL CLASS

II

NUMBER OF LUMINAIRES

2

RAL

9016

ENERGY EFFICIENCY

A+

MACADAM STEPS

<3 Step MacAdam

COLOR TEMPERATURE (K)

3000 K

L70 (°C)

20000h at 25°C

OPTICS

General 112°

CONTROL

On/Off

LIGHT BEAM APERTURE ANGLE (°)

112°

POWER FACTOR (Φ)

> 0,9

POWER (W)

6 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Trimless

REGULATIONS

EAC MARKED

Yes

ECORRAE MARKED

Yes

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0

PACKAGING LENGTH

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

0

PACKAGING NET WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0

PACKAGING WIDTH

0