

Sealing gasket square for tray IP66 Simon K45

REF. RKS003



BASIC INFORMATION

DESCRIPTION

The square Sealing gasket for IP66 tray of the series Simon K45 has dimensions of 130 x 130 x 2 mm. With design very innovative thanks to the avant-garde lines that delimit its shape, this is a product designed as a replacement of the square sealing gasket to house between the tray and the mechanism-holder unit. Does not include the mechanism-holder unit. The self-extinguishing thermoplastic and halogen-free is composed with which it has been manufactured, its resistant and durable structure. This material; guarantees no flame propagation in case of fire and the low toxicity in case of smoke, so we are looking at one of the safest elements of this range, all with the best value for money that we can find today in the sector of the products designed for electrical installations in homes and companies. With the range update, its equivalent for the new version is the KFS1002 reference.

FINISH

Black

PACKAGING CONTENTS

Square sealing gasket for IP66 tray

ETIM CLASS

EC002420

MATERIAL

Rubber

REMARKS

Replacement for sealing gasket to order as substitution for the existing one (does not include mechanism-holder unit)

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

Without perforation or
contournement with 2000 V at
50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90° C

HEAT RESISTANCE (°C)

+70°C (according to standard IEC
60670)

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP66

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 60° C

INSTALLATION AND MAINTENANCE

EXTINGUISHING (°C)

+650 °C (according to standard
IEC 60670)

TYPE OF FASTENING

By unscrewing and extracting
the mechanism-holder unit and
substituting the old sealing
gasket with the new one.

INSTALLATION DIRECTION

The sealing gasket is supplied
without a specific (symmetrical)
fitting position.

INSTALLATION TYPE

Product intended as a spare part
for the square sealing gasket
which is housed between the
tray and the mechanism-holder
unit (does not include the
mechanism-holder unit).

REGULATIONS

REGULATIONS

UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436056381

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436056381

PACKAGING VOLUME

0.33

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

10

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

220

PACKAGING NET WEIGHT

0.007

UNITARY PACKAGING GROSS
WEIGHT

0.007

PACKAGING LENGTH

150

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.007